Leica Zeno 5 **GPS** Handheld Datasheet









Power for the field without compromises

The Zeno 5 packs full functionality into an ergonomic device - making it the industry's most powerful, and rugged GPS handheld with full phone functionality. The Zeno 5 features a high-speed processor, delivering uncompromised performance, fully integrated into the Leica Zeno GIS series.

- Integrated 3.2 Megapixel camera, and hot-swappable all-day Li-Ion battery
- High-sensitivity GPS receiver supporting 2 – 5 m positional accuracy



Optimal viewing experience and ergonomics

The Zeno 5 is equipped with a 3.7" VGA colour transflective touchscreen that can be operated Pocket-size, lightweight and rugged (IP54), by finger or stylus. The display has been designed for optimal viewing, to be sunlight readable and backlit for darker conditions.

- designed for one-handed operation
- Windows® Embedded Handheld 6.5 OS allowing simple and intuitive use



Latest technology to support your field work

The Zeno 5 includes the latest wireless communication technology, light sensors, accelerometer, gyroscope, digital compass, Wi-Fi and GPS, allowing GPS-supported mapping applications with direct access to the office.

- High-speed communication standards (GSM/UMTS/CDMA, Wi-Fi and Bluetooth®)
- Automated screen rotation, to quickly view a map or document in landscape mode





Technical Specifications

reclinical Specifications	
Leica Zeno 5	
Technology	
Processor	Industrial TI AM3715 Sitara microprocessor (ARM Cortex A8) @ 800 MHz
Memory & Storage	On-board RAM: 256 MB SDRAM On-board ROM: 2 GB Flash MicroSD memory expansion slot
Operating System	Microsoft Windows® Embedded Handheld 6.5.3
Screen	3.7" VGA (480 x 640) portrait mode
	Sunlight readable with integrated touch screen (passive stylus or finger operation)
Keyboard & Buttons	Navigation key (Left, Right, Up, Down) Home key 2 x Windows Menu keys 4 x programmable keys Call and hang-up key QWERTY keypad, fully illuminated and ergonomically enhanced for one-hand operation; virtual keyboard
1/0	USB and DC Input (via SnapOn module) Docking Connector (Contact Pin Type)
Communication	
Integrated communication modules	On-board IEEE 802.11a/b/g/n (CCX V4 Certified) radio: Security, 802.1X, WPA / WPA2-Enterprise Authentication: FAST-MSCHAPV2; LEAP; PEAPV0-MSCHAPV2; PEAPV1-GTC; TLS Encryption: 64/128 WEP, AES-CCMP, TKIP Bluetooth® v2.0 + EDR radio UMTS 3.8C HSPA+ radio Five Band UMTS: 800/850, AWS, 1900, 2100 MHz Quad-Band GSM: 850, 900, 1800, 1900 MHz COMA EVDO Rev A radio Dual Band: 800/1900 MHz Integrated 5 band Antenna, supports both voice and data
Audio & Voice	Built-in 85db mono speaker and Microphone Supports VoIP, speech recognition, & Push-to-Talk applications Wireless Bluetooth® headset support Front and rear speakers
Integrated GPS ENABLED	SirfStarIV GPS with SiRFInstantFix and A-GPS support (48 channel) and active jammer removal GPS Real-Time Accuracy: 2 – 5 m / SBAS (WAAS, EGNOS, MSAS, GAGAN) ¹ : 1 – 3 m
Integrated Camera	3.2 Megapixel Colour with Auto Focus and Dual LED Flash
Standard Software	
Standard Software	Windows® Office Mobile 2010, incl. Word, Excel, PowerPoint, OneNote & SharePoint, Internet Explorer Mobile, Windows Office Outlook Mobile, Windows Media Player Mobile, Device Management Software
Power Management	
Batteries	Hot-swappable 3600 mAh Li-ion rechargeable battery (System backup during battery swap)
Power	Input: 100 – 240 VAC, 50 – 60 Hz, 5 VDC Output
Operating Time	10 h²
Battery Charging Time	2.5 h
Physical Specifications	
Size	158 mm x 78 mm x 38 mm (6.2" x 3.1" x 1.5")
Weight	375 gr (0.82 lbs), including all-day battery, stylus and handstrap
Sand, Dust & Water	IP54, IEC 529
Operating temperature range	-10°C to +50°C (14°F to 122°F)
Storage temperature range	-20°C to +65°C (-4°F to 140°F)
Humidity	5% to 95% RH non-condensing
Drop	1.5 m (5 ft) – 26 drops on each edge, corner, and face to polished concrete
Accessories and Emhanced Features	
Enhanced Features	Accelerometer Digital Compass Gyroscope Light Sensor Proximity Sensor
Accessories	 Spare 3.6 Ah Li-ion rechargeable battery Docking Station, including a Micro USB port & cable, and a spare battery charger with simultaneously capabilit to charge the device and spare battery Car charger (10 – 30 V) Hand Strap Stylus & Tether AC adaptor USB SnapOn module Pouch Pole Mount to attach the Zeno 5 on a GNSS pole
Optional Software	Leica Zeno Field
Ontional CNSS Consorr	Leica Zeno Connect Leica Zeno CCO2 plus ExpatAntonno
Optional GNSS Sensors	Leica Zeno GG02 plus SmartAntenna

- ¹ WAAS available in North America only, EGNOS available in Europe only; GAGAN available in Indian Subcontinent only; MSAS available in Japan only
- ² In continuous field operation mode, may vary with temperature, battery age etc.





Total Quality Management – our commitment to total customer satisfaction.

logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under license. Windows CE, Internet Explorer Mobile, File Explorer, Word Mobile & Microsoft Media Player are either registered trademarks or trademarks of Microsoft Corporation in the United States and / or other countries.

Other trademarks and trade names are those of their respective owners.

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland – Switzerland, 2012. 795909en – 12.13 – galledia

